

DIN-EN 857 1SC

EB71

1 Steel Wire Braid



TUBE : MINERAL, VEGETABLE AND HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : 1 HIGH TENSILE STEEL WIRE BRAID.
 COVER : OIL, ABRASION AND WEATHER RESISTANT SPECIAL SYNTHETIC RUBBER.
 APPLICATION : FOR LOW-MEDIUM PRESSURE HYDRAULIC SYSTEMS USING HYDRAULIC OILS, MINERAL AND VEGETABLE LUBRICANTS.
 TEMPERATURE RANGE : -40°C~+100°C / -40°F~+212°F

TYPE	SIZE		 ID (mm)		 ROD (mm)		 OD (mm)	 WP		 BP		 BR/r	 W	 L
	Dash Size	inch	min	max	min	max	max	bar	psi	bar	psi	mm	g/m	max/m
EB71-06	-04	1/4"	6.4	6.9	9.6	10.8	13.5	225	3263	900	13050	75	240	50/100
EB71-08	-05	5/16"	7.9	8.5	10.9	12.1	14.5	215	3118	860	12325	85	260	50/100
EB71-10	-06	3/8"	9.5	10.1	12.7	14.5	16.9	180	2610	720	10440	90	290	50/100
EB71-13	-08	1/2"	12.7	13.5	15.9	18.1	20.4	160	2320	640	9280	130	390	50/100
EB71-16	-10	5/8"	15.8	16.7	19.8	21.0	23.0	130	1885	520	7540	150	470	50/100
EB71-19	-12	3/4"	18.8	19.8	23.2	24.4	26.7	105	1523	420	6090	180	550	50/100
EB71-25	-16	1"	25.4	26.4	30.7	31.9	34.9	88	1276	352	5075	230	840	50/100





OPTIONS



MSHA

MARKING/TRANSFER TAPE, EMBOSSED OR INK JET

 **DIN-EN 857 1SC(**²)(DN**mm) W.P.**BAR/**PSI *Q/****(YEAR)**

NORMS	EN857	COLOUR				
			BLACK	BLUE	RED	GRAY